

In the Claims:

Please cancel Claim 3 without disclaimer or prejudice, amend Claims 1, 2, 4-16 and 18 and add new Claims 19-34 as follows:

1. (Currently Amended) A ~~piston pump for propelling liquid through use with a lumen of a flexible tube operably disposed therein for delivering liquid to a patient segment~~, the pump comprising:

a first tube-clamping member;

a first set of tube squeezing members;

a second tube-clamping member;

AG a second set of tube squeezing members, said first tube-clamping, first set of tube squeezing, second tube-clamping and second set of tube squeezing members being sequentially arranged in a direction from upstream to downstream;

a motor; and

a synchronizing device operably associated with ~~[[the]]~~ said motor and said first tube-clamping, first set of tube squeezing, second tube-clamping and second set of tube squeezing members, [[the]] said synchronizing device operable to activate said first tube-clamping, first set of tube squeezing, second tube-clamping and second set of tube squeezing members in a sequential order to engage the flexible tube such that fluid liquid in the flexible tube is displaced pumped in a downstream direction.

2. (Currently Amended) The ~~piston pump of claim 1, further comprising wherein the flexible tube comprises a disposal flow set comprising~~ a drip chamber, a valve, and a

~~flexible tube including at least one squeezing segment defining two ends, said tube-~~
~~clamping and tube squeezing members being adapted to engage the at least one squeezing~~
~~segment wherein each end of the at least one squeezing segment is associated with a~~
~~stopper.~~

3. (Canceled)

A3
4. (Currently Amended) The ~~piston~~ pump of claim [[3]] 1 wherein each member of
said first and second set of tube squeezing members comprises a [[the]] pressing surface of
~~said squeezing members is designed for designed squeezing adapted to constrict the flexible~~
tube.

5. (Currently Amended) The ~~piston~~ pump of claim [[3]] 1 wherein the squeezing
area defined by [[of]] said first set of squeezing members is about twice that of the
squeezing area [[of]] defined by said second set of squeezing members.

6. (Currently Amended) The ~~piston~~ pump of claim [[3]] 1 wherein [[the]] said
synchronizing device comprises an axis axle and a number plurality of eccentric cams
operably associated with the axis axle, a cam for each of the plurality of cams adapted to
engage a respective member of said clamping or squeezing members, for moving said
members up and down.

7. (Currently Amended) The ~~piston~~ pump of claim 6 wherein ~~[[the]]~~ said motor is operable to revolve said synchronizing device.

8. (Currently Amended) The ~~piston~~ pump of claim 1, further comprising an ultrasonic sensor operably associated with the flexible tube ~~segment~~ for detecting air therein ~~in the liquid~~.

A3
9. (Currently Amended) The ~~piston~~ pump of claim 1, further comprising a communication device in communication with the motor and operable to ~~use any~~ ~~communication infrastructure for delivering~~ deliver information and ~~receiving~~ receive commands.

10. (Currently Amended) The ~~piston~~ pump of claim 2, ~~further comprising wherein~~ the flexible tube further comprises a dripping drip sensor for sensing and counting the drips passing through said ~~dripping drip~~ chamber.

11. (Currently Amended) The ~~piston~~ pump of claim ~~[[2]]~~ 1, further comprising a sensor unit adapted for determining the pressure of a liquid flowing within said flexible tube.

12. (Currently Amended) The ~~piston~~ pump of claim 11 wherein the sensor unit defines a tube receiving space formed by walls engaging at least a portion of said flexible

tube and comprises a sensing member projecting into the space for determining deformation-resistance of said flexible tube.

13. (Currently Amended) The piston pump of claim 12 wherein said sensing member comprises a plunger associated with a strain gage, and said tube receiving space is defined by a rectangular shape and said plunger projects through one of the walls [[of]] defining said tube receiving space.

A3
14. (Currently Amended) The piston pump of claim 7, further comprising a controller for controlling said motor ~~wherein said motor is revolved by a controller into a nonlinear revolution~~ to achieve linear flow of liquid within the flexible tube, said controller [[by]] using an algorithm for revolving [[a]] said motor in a specific nonlinear revolution, the algorithm adapted to comprising:

divide the motor revolution ~~is divided~~ into a number of steps;

~~a controller rotates~~ rotate said motor, sequentially from first step to the last step of each revolution, wherein each step or a group of steps has an individual speed and an individual pause time between steps or a group of steps;

measure the liquid flow, in the output of the pump, ~~is measured~~ in each said step and in each said pause;

~~calculating or changing~~ calculate or change the speed of each said step and the duration of each said pause, to have achieve the desired flow function; and

~~storing store in a memory~~ the flow function of the nonlinear revolution of said motor, ~~in a memory~~.

15. (Currently Amended) The ~~piston~~ pump of claim [[13]] 14, wherein said algorithm is used sequentially during the operation of the pump ~~said pump work~~.

16. (Currently Amended) The ~~piston~~ pump of claim 15 wherein said algorithm is used for calibration to obtain said flow function of nonlinear revolution and said controller uses the obtained function to revolve said motor in further operation of the pump ~~work~~.

A3
17. (Original) A method for controlling a pump in which a flexible tube is disposed for delivery of a liquid, comprising:

activating a second tube-clamping member into blocking a lumen of the tube and a first tube-clamping member to open the lumen of the tube;

activating a second set of tube squeezing members to constrict a second portion of the tube and a first set of tube squeezing members to allow expansion of a first portion of the tube;

activating the first tube-clamping member into blocking the lumen of the tube;

activating the second clamping member to open the lumen of the tube, and the second set of tube squeezing members to allow expansion of the second portion of the tube;
and

activating the first set of tube squeezing members to constrict the first portion of the tube.

18. (Currently Amended) An injection apparatus comprising, in combination, a pump for pumping liquid through a ~~lumen of~~ a flexible tube;

wherein the pump comprises:

a motor;

a first tube-clamping member;

a first set of tube squeezing members;

a second tube-clamping member;

AB
a second set of tube squeezing members, said first tube-clamping, first set of tube squeezing, second tube-clamping and second set of tube squeezing members being sequentially arranged in a direction from upstream to downstream; and

a synchronizing device operably associated with ~~[[the]]~~ said motor and said first tube-clamping, first set of tube squeezing, second tube-clamping and second set of tube squeezing members, [[the]] said synchronizing device operable to activate said first tube-clamping, first set of tube squeezing, second tube-clamping and second set of tube squeezing members in a sequential order to engage the flexible tube such that fluid in the flexible tube is ~~displaced~~ pumped in a downstream direction; and

wherein the flexible tube comprises:

~~a drip chamber;~~

~~a valve; and~~

at least one squeezing segment operable to be engaged by said first tube-clamping, first set of tube squeezing, second tube-clamping and second set of tube squeezing members to pump fluid within the flexible tube in a downstream direction

~~defining two ends, wherein each end of the at least one squeezing segment is associated with a stopper.~~

19. (New) The pump of claim 1 wherein said first set of tube squeezing members comprises four tube squeezing members and said second set of tube squeezing members comprises two tube squeezing members.

A3
20. (New) The pump of claim 1 wherein said first and second tube-clamping members are adapted to block the flexible tube and said first and second set of tube squeezing members are adapted to constrict the flexible tube.

21. (New) The pump of claim 1 wherein each of said first and second tube-clamping members comprises a blade surface adapted to block the flexible tube.

22. (New) The injection apparatus of claim 18 wherein the squeezing area defined by said first set of squeezing members is about twice that of the squeezing area defined by said second set of squeezing members.

23. (New) The injection apparatus of claim 18 wherein said synchronizing device comprises an axle and a plurality of eccentric cams operably associated with the axle, each of the plurality of cams adapted to engage a respective member of said clamping or squeezing members.

24. (New) The injection apparatus of claim 18 wherein said first set of tube squeezing members comprises four tube squeezing members and said second set of tube squeezing members comprises two tube squeezing members.

25. (New) The injection apparatus of claim 18 wherein said first and second tube-clamping members are adapted to block the flexible tube and said first and second set of tube squeezing members are adapted to constrict the flexible tube.

26. (New) The injection apparatus of claim 18 wherein each of said first and second tube-clamping members comprises a blade surface adapted to block the flexible tube.

27. (New) An injection apparatus comprising a pump and a flexible tube for use with the pump, wherein the pump comprises:

- a first tube-clamping member adapted to block the flexible tube;
- a first plurality of tube squeezing members adapted to constrict the flexible tube;
- a second tube-clamping member adapted to block the flexible tube; and
- a second plurality of tube squeezing members adapted to constrict the flexible

tube, said first tube-clamping, first plurality of tube squeezing, second tube-clamping and second plurality of tube squeezing members being sequentially arranged in a direction from upstream to downstream; and

wherein the flexible tube comprises at least one squeezing segment operable to be engaged by said first tube-clamping, first plurality of tube squeezing, second tube-

clamping and second plurality of tube squeezing members to pump fluid within the flexible tube in a downstream direction.

28. (New) The injection apparatus of claim 27 wherein the pump further comprises a motor and a synchronizing device operably associated with said motor and said first tube-clamping, first plurality of tube squeezing, second tube-clamping and second plurality of tube squeezing members, said synchronizing device operable to activate said first tube-clamping, first plurality of tube squeezing, second tube-clamping and second plurality of tube squeezing members in a sequential order to engage the flexible tube such that fluid in the flexible tube is pumped in a downstream direction

29. (New) The injection apparatus of claim 27 wherein the squeezing area defined by said first plurality of squeezing members is about twice that of the squeezing area defined by said second plurality of squeezing members.

30. (New) The injection apparatus of claim 28 wherein said synchronizing device comprises an axle and a plurality of eccentric cams operably associated with the axle, each of the plurality of cams adapted to engage a respective member of said clamping or squeezing members.

31. (New) The injection apparatus of claim 27 wherein said first plurality of tube squeezing members comprises four tube squeezing members and said second plurality of tube squeezing members comprises two tube squeezing members.

A3

32. (New) The injection apparatus of claim 27 wherein each member of said first and second plurality of tube squeezing members comprises a pressing surface adapted to constrict the flexible tube.

33. (New) The injection apparatus of claim 27 wherein each of said first and second tube-clamping members comprises a blade surface adapted to block the flexible tube.

34. (New) The pump of Claim 2 wherein each end of the at least one squeezing segment is associated with a stopper.
